

AURA-6906W



Features:

- Android, iOS and Windows support
- Comes with Embedded Linux + Embedded HTTP Server
- LAN and WIFI 2-in-1 interface
- Allows OS independent printing from SOAP/HTTP-supported devices
- No separate web server is required for printing

Specification

Parper width	80mm	58mm
Interface	Ethernet, Wireless LAN	
Resolution	180 dpi x 180 dpi (W x H)	
Print Width	512 dots	424dots
Font	Font A, Font B	
Default Line Feed Space	30 dots	
Color Specification	Black only	
Raster Image	Monochrome image	
Logo	Monochrome image	
Bar Code <barcode>	UPC-A, UPCE, EAN13, JAN13, EAN8, JAN8, CODE39, ITF, CODABAR, CODE93, CODE128	
Two-Dimensional Code <symbol>	PDF417, QR Code	
Page Mode Default Area	512 dots x 834 dots (W x H)	360 dots x 834 dots (W x H)
Page Mode Maximum Area	512 dots x 834 dots (W x H)	360 dots x 834 dots (W x H)
Paper Cut <cut>	cut, Feed cut	
Drawer Kick-Out <pulse>	Supported	
Forced transmission mode	Supported	
Recovery from an error <recovery>	Supported	
Reset <reset>	Supported	
Command <command>	Supported	
Characters in a Line		
Font A	ANK : 42 characters	ANK : 35 characters
Font B	ANK : 56 characters	ANK : 47 characters
Character Size		
Font A	ANK : 12 dots x 24 dots (W x H)	
Font B	ANK : 8 dots x 16 dots (W x H)	
Character Baseline		
Font A	ANK : 12 dots x 24 dots (W x H)	
Font B	ANK : 8 dots x 16 dots (W x H)	

Let your business go mobile with ease



AURA-6906W

Web Printer

AURA-6906W features a web server technology that enables web based printing from virtually any Android, iOS or Windows based device.



Design and Manufacturing in Taiwan by Posiflex Technology Inc.
The product information and specifications are subject to change without prior notice.

2015Q1



POSIFLEX TECHNOLOGY INC.
No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan
Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw
Fax : +886-2-2299-1819 www.posiflex.com

Authorized Distributor / Reseller